



ELISHA[®] CLEANER

Elisha[®] Cleaner is a low V.O.C., fast-acting, readily biodegradable cleaner. Lifts heavy grease, oil, synthetic oil, and preservatives. Cleans accumulated cutting fluids and petroleum residues. Developed to remove and clean up the E-products. Biodegradable, non-petroleum, high flash point, low V.O.C., maximum strength formulation is ready-to-use. Clean up any residue with soap and water.

<u>TEST METHOD</u>	<u>DESCRIPTION</u>	<u>RESULTS</u>
ASTM E-659	Autoignition Temperature	253°C
	Ignition Delay Time	136.5 seconds
	Barometric Pressure	757 mm Hg
ASTM D-92	Flash Point & Fire Point *occurred simultaneously	245°F*
ASTM D-93	Flash Point	184°F
ASTM D-1218	Refractive Index	1.45775@25°C
ASTM D-1120	Boiling Point	528°F @ 761 mm Hg
ASTM D-1177	Freezing Point	No Distinct Inflections
ASTM D-2879	Vapor Pressure @ 25°C	1.8 mm Hg
ASTM D-1298	Specific Gravity	29.2 @ 60°F

Ingredients are E.P.A. listed as approved replacement chemical for solvent usage.

DISPOSE OF CLEANING RESIDUES IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS.

DeNOVUS

P.O. Box 755, Ennis, TX 75120
TELE: (214) 789-5725, Fax (972) 875-9425
www.DeNovus.com

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of DeNOVUS products are not to be construed as recommending the infringement of any patent.

Revision Date: January 13, 2017